

6. Requiring atleast 2 people, flip table back to up right position.

\* Heavy load: Caution must be taken when turning table up right. Where additional heavy is recommended.

## NOTE:

Please carefully read through instructions once before proceeding with assembly.

- (1) Heavy load, 2 or more adults are recommended to assemble.
- (2) Proper lifting posture is recommended to avoid injuries.
- (3) Table contains small parts & components not suitable for children.
- (4) Table contains joints and folding parts. Care should be taken durable stowage & assembly
- (5) Products is free standing. Efforts should be made to ensure product is used on even surface.

## COMPONENTS:

| Part Description                    | Quantity |
|-------------------------------------|----------|
| ① Bolt: 5/16" x 2½" (Thickest Bolt) | 12       |
| ② Washer: 5/16"                     | 12       |
| ③ Leg Leveller                      | 4        |
| ④ Bolt: ¼" x 3"                     | 8        |
| ⑤ Bolt: ¼" x 2½"                    | 8        |
| ⑥ Washer: ¼"                        | 24       |
| ⑦ Locking Nut ¼" x ½"               | 8        |
| ⑧ Side Leg Panels                   | 2        |
| ⑨ Legs                              | 4        |
| ⑩ Side Leg Panels                   | 2        |
| ⑪ Barrel Nuts                       | 8        |

1. Place table face door on smooth even surface.

\* Ensure assembly surface is free of any debris.

\* Carton box top can be used to line floor surface to reduce chance of scratching table.

2. Secure legs to table base.

\* Note curved side facing outwards

\* Each leg is secured by three (3) bolts and washers ① and ②

\* Repeat for all four (4) legs.

3. Screw in table leg leveller base

\* Do NOT over fasten or tighten. Adjustment may be required to adjust table height and levels.

4. Insert end leg panel between table legs, and secure with bolt, washer and barrel nut.

\* Place barrel nuts into pre-cut holes in end leg panel. ①

\* With pre-drilled holes in both leg and end panel aligned, thread bolt through washer and leg panel. ②

\* Secure bolt by threading and tightening into barrel nut in endleg panel.

\* Repeat for two (2) bolts per leg x all four (4) legs.

5. Place side leg panels in the inner part of the legs ③

\* Thread bolt with washer through both leg panel and side panel from the outside.

\* Secure bolt by screwing on additional washer and locking nut from inner side.

\* Repeat for two (2) bolts per leg x all four (4) legs.

